

EMC/RFI High Performance Filter



- Rated current 50A to 150A
- Industry standard noise filter for three-phase power drive systems
- Low profile type
- Block terminal with safety cover



Technical Specifications

Maximum continuous operating voltage	3x520/300 VAC
Nominal operating voltage	480 VAC
Rated currents	50 to 150 A @ 50°C
Overload capability	4x rated current at switch on, 1.5x rated current for 1 minute, once per hour
Operating frequency	DC to 60 Hz
High potential test voltage	P → E 3000 VAC for 2 sec P → P 2250 VDC for 2 sec
Temperature range (operation and storage)	-25°C to +100°C (25/100/21)
Protection category	IP 00 (acc. IEC 60529-1)
Flammability corresponding to	UL 94 V-0
Design corresponding to	UL 1283, CSA 22.2 No. 8 1986, IEC/EN 60939
MTBF (Mil-HB-217F)	>410,000 h @ 50°C/480 V

Approvals & Compliances




Features and Benefits

- Satisfies the low leakage current required for Japanese delta-connected power supplies.
- Adopts advanced dual stage circuitry for high attenuation
- Complies with Class A limits
- Low profile design allows for smooth storage in the tight spaces inside machines
- Comes with terminal block with safety covers
- Rated for 520VAC, suitable for a variety of applications around the world

Typical Applications

- Three-phase variable speed drives and power drive systems (PDS)
- Product equipment including energy conversion devices (inverters, converters)
- Process automation equipment
- Three-phase power supplies and uninterruptable power supplies (UPS)
- Applications requiring low leakage current

Typical electrical schematic



Filter Selection Table

Filter	Rated current	Leakage current*	Leakage current	Typical Power loss***	Weight	Input/Output
	@ 50°C	520 V/50 Hz	250V/60Hz** corner grounded	@ 25°C		connections
	[A]	[mA]	[mA]	[W]	[kg]	
Standard Housing						
FN3021-50-55	50	0.06	1.75	28	3.8	-55
FN3021-80-55	80	0.06	1.75	36	4.6	-55
FN3021-100-56	100	0.06	1.75	41	5.9	-56
FN3021-150-56	150	0.06	1.75	68	7.5	-56





* Maximum leakage current under normal operating conditions (acc. to IEC60939-3).

** Leakage current for delta network grids, with one corner grounded


*** Power Loss [W] calculated: $3 \cdot \text{RatedCurrent}^2 \cdot \text{Max.DCRes}$

Typical Filter Attenuation

Per CISPR 17; A=50 Ω/50 Ω sym; B=50 Ω/50 Ω asym



Mechanical Data





Dimensions

	50 A	80 A	100 A	150 A
A	390	445	475	510
B	160	165	170	190
C	70	70	80	90
D	334	389	414	449
E	370	418	450	490
F	135	141	135	160
G1	Ø6.5	Ø6.5	Ø6.5	Ø6.5
G2	13 x 6.5	13 x 6.5	13 x 6.5	13 x 6.5
H	1.5	1.5	1.5	M6
I	30	30	33.5	33.5
J	M6	M6	M8	M8

All dimensions in mm; 1 inch = 25.4 mm
Tolerances according: ISO 2768-m/EN 22768-m

Please visit www.schaffner.com to find more details on filter connections.

Filter Input/Output Connector Cross Sections

	-55 (50 A and 80 A)	-56 (100 A and 150 A)
Ring/fork lug (W/d)*	 max. 16 mm/min. Ø6.3 mm	 max. 20 mm/min. Ø8.3 mm
Recommended torque	5.2 - 5.7 Nm	10 - 11 Nm

*Schaffner recommends the use of insulated and UL-recognized ring lugs or fork lugs of the appropriate size.

Headquarters, Global Innovation and Development

Switzerland

Schaffner Group

Industrie Nord
Nordstrasse 5
4542
Luterbach
+41 32 681 66 26
info@schaffner.com

Sales and Application Centers

Finland

Schaffner Oy

Lohjanharjuntie 1109
08500
Lohja
+ 358 50 468 72 84
finlandsales@schaffner.com

France

Schaffner EMC S.A.S.

16-20 Rue Louis Rameau
95875
Bezons
+33 1 34 34 30 60
francesales@schaffner.com

Germany

Schaffner Deutschland GmbH

Ohiostr. 8
76149
Karlsruhe
+49 721 56910
germanysales@schaffner.com

Italy

Schaffner EMC S.r.l.

Via Ticino, 30
20900
Monza (MB)
+39 335 120 44 32
italysales@schaffner.com

United States

Schaffner EMC Inc.

52 Mayfield Avenue
Edison, New Jersey
+1 732 225 9533
usasales@schaffner.com

Japan

Schaffner EMC K.K.

ISM Sangenjaya 7F
1-32-12 Kamiyama Setagaya-ku
154-0011
Tokyo
+81 3 5712 3650
japansales@schaffner.com

Sweden

Schaffner EMC AB

Östermalmströgr 1
114 42
Stockholm
+46 8 5050 2425
swedensales@schaffner.com

Switzerland

Schaffner EMV AG

Industrie Nord
Nordstrasse 5
4542
Luterbach
+41 32 681 66 26
switzerlandsales@schaffner.com

India

Schaffner India Pvt. Ltd

Regus World Trade Centre
WTC 22nd Floor Unit No 2238 Brigade
Gateway Campus 26/1 Dr. Rajkumar Road
Malleshwaram (W)
560055
Bangalore
+91 8067935355
indiasales@schaffner.com

United Kingdom

Schaffner Ltd.

Suite 1 Oakmede Place
Terrace Road
RG42 4JF
Binfield
+44 118 9770070
schaffner.uksales@te.com

Singapore

Schaffner EMC Pte Ltd.

Blk 3015A Ubi Road 1 #05-09 Kampong Ubi
Industrial Estate
408705
Singapore
+65 63773283
singaporesales@schaffner.com

To find your local partner within Schaffner's global network schaffner.com

© 2025 Schaffner Group

The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.